TABLE 2
Deterministic Exposure Factors – Construction Workers

Parameter	Abbrev.	Value	Units	Reference			
Dermal absorption fraction	ABS	chemical-specific		USEPA 2004c			
Dermal adherence factor, soil	AF_{cw}	0.3	mg/cm ²	USEPA 2002a			
Averaging time, carcinogenic	AT_c	70	years	USEPA 2002a			
Averaging time, carcinogenic for inhalation exposures	AT_c	613200	hours				
Averaging time, non-carcinogenic	AT_{nc}	1	years	Based on ED _{cw}			
Averaging time, non-carcinogenic for inhalation exposures	AT_{nc}	8760	hours				
Relative bioavailability	BIO	chemical-specific					
Adult body weight	BW	70	kg	USEPA 2002a			
Exposure frequency, soil	EF_{cw}	250	days/year	USEPA 2002a			
Exposure duration	ED_{cw}	1	years	(1)			
Construction worker exposed surface area, soil	SA	3,300	cm ² /day	USEPA 2002a			
Construction worker soil ingestion rate	IR _{cw}	330	mg/day	USEPA 2002a			
Exposure time, indoors	ET_i	0	hours/day	(2)			
Exposure time, outdoors	ETo	8	hours/day	(2)			
Conversion factor	CF ₁	1000	ug/mg				
Conversion factor	CF ₂	1000	g/kg				
Conversion factor	CF ₃	1000000	cm ³ /m ³				
Conversion factor	CF ₄	1E-06	kg/mg				
Radionuclide-Specific Factors							
Conversion factor	CF_2	1000	g/kg				
Conversion factor	CF ₅	0.001	g/mg				
Conversion factor	CF_{DY}	365	days/year				
Conversion factor	CF _{HD}	24	hours/day				
Inhalation rate, adult	InhR	0.833	m ³ /hour	USEPA 2002a			
Construction worker area correction factor	ACF	site specific		(3)			
Gamma shielding factor	GSF	0.4	unitless	USEPA 2000a, 2009a			

⁽¹⁾ Based on site data. A one-year exposure duration is appropriate for carcinogenic effects, because the methodology averages exposures over a lifetime (see USEPA 2002a).

⁽⁵⁾ Assumes worker spends 100% of time outdoors, 8 hours a day.

TABLE 2
Deterministic Exposure Factors – Construction Workers

Parameter	Abbrev.	Value	Units	Reference

⁽³⁾ A value of 1.0 applies to sites of 1 ha size or larger. ACF values for smaller sites are available from Table 5-1 of the Technical Background Document of USEPA 2000a.